

# TECHNICAL CHARACTERISTICS

## SELENIA TURBO DIESEL 10W-40

PRODUCT CODE: 1091

### APPLICATION

Synthetic based motor oil for diesel cars equipped turbo-charged or multi-valve indirect or direct injection engines. Also ideal for aspirated diesel cars.

### SPECIFICATIONS

SAE 10W-40, ACEA B3, API CD/SF, CCMC PD2, VW 505.00, MIL-L-2104D LEVEL, FIAT 9.55535

### TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUES
APPEARANCE	--	--	B. & C.
SPECIFIC GRAVITY @ 15°C	ASTM D 1298	--	0,878
VISCOSITY @ 100°C	ASTM D 445	cSt	14,8
VISCOSITY INDEX	ASTM D 2270	--	155
SULFATED ASH	ASTM D 874	%	1,1
FLASH POINT Cl. O. C.	ASTM D 92	°C	210
T.B.N.	ASTM D 2896	mg KOH/g	9,5
POUR POINT	ASTM D 97	°C	-30
FOAM @ 24°C	ASTM D 892	cc/s	TRACCES/0

RESEARCH & DEVELOPMENT

01/2004

All technical data is provided for reference only.



**FL SELENIA s.p.a.**

Sede Legale:  
Via Santena, 1  
10029 Villastellone (Torino)  
Tel. +39 011.96131  
Fax +39 011.9613555

Cap. Soc. €2.000.000 i.v.  
Partita IVA 00844490151  
Cod. Fisc. 00844490151  
Reg. Imp. Torino 00844490151  
www.flselenia.com