

URANIA TURBO LD

DESCRIPTION

Mineral based engine oil. For industrial vehicles with turbo engines of every type and power rating. Also ideal for industrial vehicles with aspirated engines and commercial vehicles. URANIA TURBO LD has been created and developed by FL using the vastest engine experience available today to meet the requirement of Iveco for new generation engines. Moreover it can guarantee a reduction in oil consumption of up to 30%.

CHARACTERISTICS

The main characteristic of URANIA TURBO LD are:
Longer change interval up to 50,000 km and beyond;
Engine protection increased by 50% against pollution or acid components from the combustion of diesel fuels with a high sulphur content.
It also ensures:

Maximum protection against wear caused by the continuous engine performance in conditions with heavy loads;

Maximum protection against deposits (lacquer, sludge and other pollutants) caused by high running temperatures;

Easy cold start, as well as high and constant pressure in the lubricant circuit at all working and climatic temperatures.

As it exceeds the quality requirements of all the European Manufacturers of industrial vehicles, URANIA TURBO LD can be used for turbo-charged or aspirated diesel engines of every type, make and power rating.



ADVICE ON USE

Replacement as indicated by the Manufacturer, recommended oil changes are:

Up to 20,000 km on vehicles operating under heavy-duty conditions

Up to 50,000 km and beyond on vehicles in road/long distance service.

RECOMMENDED BY

Iveco, AIFO.

APPROVED BY

Mercedes, Volvo, Man, Mack.

TECHNICAL DATA

ACEA E3, ALLISON C4, API CF, IVECO 18-1804, MAN QC 13-017/M3275, MB 228.3, RENAULT RVI RD Performance, SAE 15W-40, VOLVO VDS 2